

party with the angular pointing restriction necessary to meet the horizontal emission limit specified in paragraph (b).

(g) In addition to the information required in subpart J of part 2, the application for certification shall contain:

(1) Measurements of field strength per MHz along with the intermediate frequency of the spectrum analyzer or equivalent measuring receiver;

(2) The angular separation between the direction at which maximum field strength occurs and the direction at which the field strength is reduced to 400 microvolts/meter/MHz at 3 meters;

(3) A photograph of the spectrum analyzer display showing the entire swept frequency signal and a calibrated scale for the vertical and horizontal axes; the spectrum analyzer settings that were used shall be labelled on the photograph; and,

(4) The results of the frequency search for spurious and sideband emissions from 30 MHz to 20 GHz, exclusive of the swept frequency band, with the measuring instrument as close as possible to the unit under test.

[54 FR 17714, Apr. 25, 1989; 54 FR 32340, Aug. 7, 1989]

§ 15.252 Operation of wideband vehicular radar systems within the bands 16.2–17.7 GHz and 23.12–29.0 GHz.

(a) Operation under this section is limited to field disturbance sensors that are mounted in terrestrial transportation vehicles. Terrestrial use is limited to earth surface-based, non-aviation applications. Operation within the 16.2–17.7 GHz band is limited to field disturbance sensors that are used only for back-up assistance and that operate only when the vehicle is engaged in reverse.

(1) The –10 dB bandwidth of the fundamental emission shall be located within the 16.2–17.7 GHz band or within the 23.12–29.0 GHz band, exclusive of the 23.6–24.0 GHz restricted band, as appropriate, under all conditions of operation including the effects from stepped frequency, frequency hopping or other modulation techniques that may be employed as well as the frequency stability of the transmitter

over expected variations in temperature and supply voltage.

(2) The –10 dB bandwidth of the fundamental emission shall be 10 MHz or greater. For transmitters that employ frequency hopping, stepped frequency or similar modulation types, measurement of the –10 dB minimum bandwidth specified in this paragraph shall be made with the frequency hop or step function disabled and with the transmitter operating continuously at a fundamental frequency following the provisions of § 15.31(m).

(3) For systems operating in the 23.12–29.0 GHz band, the frequencies at which the highest average emission level and at which the highest peak level emission appear shall be greater than 24.075 GHz.

(4) These devices shall operate only when the vehicle is operating, e.g., the engine is running. Operation shall occur only upon specific activation, such as upon starting the vehicle, changing gears, or engaging a turn signal. The operation of these devices shall be related to the proper functioning of the transportation vehicle, e.g., collision avoidance.

(b) Emissions from a transmitter operating under this section shall not exceed the following equivalent isotropically radiated power (EIRP) density levels:

(1) For transmitters operating in the 16.2–17.7 GHz band, the RMS average radiated emissions above 960 MHz from a device operating under the provisions of this section shall not exceed the following EIRP limits based on measurements using a 1 MHz resolution bandwidth:

Frequency in MHz	EIRP in dBm
960–1610	–75.3
1610–16,200	–61.3
16,200–17,700	–41.3
Above 17,700	–61.3

(2) For transmitters operating in the 23.12–29.0 GHz band, the RMS average radiated emissions above 960 MHz from a device operating under the provisions of this section shall not exceed the following EIRP limits based on measurements using a 1 MHz resolution bandwidth:

§ 15.252

47 CFR Ch. I (10–1–13 Edition)

Frequency in MHz	EIRP in dBm
960–1610	–75.3
1610–23,120	–61.3
23,120–23,600	–41.3
23,600–24,000	–61.3
24,000–29,000	–41.3
Above 29,000	–61.3

(3) In addition to the radiated emission limits specified in the tables in paragraphs (b)(1) and (b)(2) of this section, transmitters operating under the provisions of this section shall not exceed the following RMS average EIRP limits when measured using a resolution bandwidth of no less than 1 kHz:

Frequency in MHz	EIRP in dBm
1164–1240	–85.3
1559–1610	–85.3

(4) There is a limit on the peak level of the emissions contained within a 50 MHz bandwidth centered on the frequency at which the highest radiated emission occurs and this 50 MHz bandwidth must be contained within the 16.2–17.7 GHz band or the 24.05–29.0 GHz band, as appropriate. The peak EIRP limit is $20 \log (\text{RBW}/50)$ dBm where RBW is the resolution bandwidth in MHz employed by the measurement instrument. RBW shall not be lower than 1 MHz or greater than 50 MHz. Further, RBW shall not be greater than the –10 dB bandwidth of the device under test. For transmitters that employ frequency hopping, stepped frequency or similar modulation types, measurement of the –10 dB minimum bandwidth specified in this paragraph shall be made with the frequency hop or step function disabled and with the transmitter operating continuously at a fundamental frequency. The video bandwidth of the measurement instrument shall not be less than RBW. The limit on peak emissions applies to the 50 MHz bandwidth centered on the frequency at which the highest level radiated emission occurs. If RBW is greater than 3 MHz, the application for certification shall contain a detailed description of the test procedure, the instrumentation employed in the testing, and the calibration of the test setup.

(5) Radiated emissions at or below 960 MHz shall not exceed the emission levels in § 15.209.

(6) Emissions from digital circuitry used to enable the operation of the transmitter may comply with the limits in § 15.209 provided it can be clearly demonstrated that those emissions are due solely to emissions from digital circuitry contained within the transmitter and the emissions are not intended to be radiated from the transmitter's antenna. Emissions from associated digital devices, as defined in § 15.3(k), e.g., emissions from digital circuitry used to control additional functions or capabilities other than the operation of the transmitter, are subject to the limits contained in subpart B of this part. Emissions from these digital circuits shall not be employed in determining the –10 dB bandwidth of the fundamental emission or the frequency at which the highest emission level occurs.

(c) Measurement procedures:

(1) All emissions at and below 960 MHz are based on measurements employing a CISPR quasi-peak detector. Unless otherwise specified, all RMS average emission levels specified in this section are to be measured utilizing a 1 MHz resolution bandwidth with a one millisecond dwell over each 1 MHz segment. The frequency span of the analyzer should equal the number of sampling bins times 1 MHz and the sweep rate of the analyzer should equal the number of sampling bins times one millisecond. The provision in § 15.35(c) that allows emissions to be averaged over a 100 millisecond period does not apply to devices operating under this section. The video bandwidth of the measurement instrument shall not be less than the resolution bandwidth and trace averaging shall not be employed. The RMS average emission measurement is to be repeated over multiple sweeps with the analyzer set for maximum hold until the amplitude stabilizes.

(2) The peak emission measurement is to be repeated over multiple sweeps with the analyzer set for maximum hold until the amplitude stabilizes.

(3) For transmitters that employ frequency hopping, stepped frequency or similar modulation types, the peak emission level measurement, the measurement of the RMS average emission levels, the measurement to determine

the center frequency, and the measurement to determine the frequency at which the highest level emission occurs shall be made with the frequency hop or step function active. Gated signals may be measured with the gating active. The provisions of §15.31(c) continue to apply to transmitters that employ swept frequency modulation.

(4) The -10 dB bandwidth is based on measurement using a peak detector, a 1 MHz resolution bandwidth, and a video bandwidth greater than or equal to the resolution bandwidth.

(5) Alternative measurement procedures may be considered by the Commission.

[70 FR 6775, Feb. 9, 2005]

§ 15.253 Operation within the bands 46.7–46.9 GHz and 76.0–77.0 GHz.

(a) Operation within the band 46.7–46.9 GHz is restricted to vehicle-mounted field disturbance sensors used as vehicle radar systems. The transmission of additional information, such as data, is permitted provided the primary mode of operation is as a vehicle-mounted field disturbance sensor. Operation under the provisions of this section is not permitted on aircraft or satellites.

(b) The radiated emission limits within the bands 46.7–46.9 GHz are as follows:

(1) If the vehicle is not in motion, the power density of any emission within the bands specified in this section shall not exceed 200 nW/cm^2 at a distance of 3 meters from the exterior surface of the radiating structure.

(2) For forward-looking vehicle mounted field disturbance sensors, if the vehicle is in motion the power density of any emission within the bands specified in this section shall not exceed $60 \text{ } \mu\text{W/cm}^2$ at a distance of 3 meters from the exterior surface of the radiating structure.

(3) For side-looking or rear-looking vehicle-mounted field disturbance sensors, if the vehicle is in motion the power density of any emission within the bands specified in this section shall not exceed $30 \text{ } \mu\text{W/cm}^2$ at a distance of 3 meters from the exterior surface of the radiating structure.

(4) The provisions in §15.35 limiting peak emissions apply.

(c) Operation within the band 76.0–77.0 GHz is restricted to vehicle-mounted field disturbance sensors used as vehicle radar systems and to fixed radar systems used at airport locations for foreign object debris detection on runways and for monitoring aircraft as well as service vehicles on taxiways and other airport vehicle service areas that have no public vehicle access. The transmission of additional information, such as data, is permitted provided the primary mode of operation is as a field disturbance sensor. Operation under the provisions of this section is not permitted on aircraft or satellites.

(d) The radiated emission limits within the band 76.0–77.0 GHz are as follows:

(1) The average power density of any emission within the bands specified in this section shall not exceed $88 \text{ } \mu\text{W/cm}^2$ at a distance of 3 meters from the exterior surface of the radiating structure (average EIRP of 50 dBm).

(2) The peak power density of any emission within the band 76–77 GHz shall not exceed $279 \text{ } \mu\text{W/cm}^2$ at a distance of 3 meters from the exterior surface of the radiating structure (peak EIRP of 55 dBm).

(e) The power density of any emissions outside the operating band shall consist solely of spurious emissions and shall not exceed the following:

(1) Radiated emissions below 40 GHz shall not exceed the general limits in §15.209.

(2) Radiated emissions outside the operating band and between 40 GHz and 200 GHz shall not exceed the following:

(i) For field disturbance sensors operating in the band 46.7–46.9 GHz: 2 pW/cm^2 at a distance of 3 meters from the exterior surface of the radiating structure.

(ii) For field disturbance sensors operating in the band 76–77 GHz: 600 pW/cm^2 at a distance of 3 meters from the exterior surface of the radiating structure.

(3) For radiated emissions above 200 GHz from field disturbance sensors operating in the 76–77 GHz band: the power density of any emission shall not exceed 1000 pW/cm^2 at a distance of 3 meters from the exterior surface of the radiating structure.